

GNU/Linux Administration - Feature #744

Add a Catchall Account Per Domain on iRedMail

02/09/2016 07:02 PM - Daniel Curtis

Status:	Closed	Start date:	02/09/2016
Priority:	Normal	Due date:	
Assignee:	Daniel Curtis	% Done:	100%
Category:	Mail Server	Estimated time:	0.50 hour
Target version:	*nix	Spent time:	0.50 hour

Description

This is a simple feature to add a catchall email account to iRedMail.

With default setting, iRedMail will reject emails sent to non-existing mail accounts under hosted mail domains. If you want to accept these emails, you need a domain catch-all account.

- With MySQL/MariaDB or PostgreSQL backend, to add a catch-all account for existing domain example.com, log into the mysql database:

```
mysql -u root -p
```

- And add the following in SQL table vmail.alias:

```
USE vmail;  
INSERT INTO alias (address, goto, domain) VALUES ('example.com', 'catchall@example.com', 'example.com');
```

This SQL command creates catchall address for domain example.com, all mails sent to non-existing accounts under example.com will be delivered to catchall@example.com.

Resources

- <http://www.iredmail.org/docs/sql.create.catch-all.html>
- <http://www.iredmail.org/forum/topic3621-iredmail-support-catchall-email-setup-in-iredmail-081-mysql.html>

History

#1 - 02/09/2016 07:14 PM - Daniel Curtis

- Description updated
- Status changed from New to Resolved
- % Done changed from 0 to 100

#2 - 02/20/2016 07:37 PM - Daniel Curtis

- Status changed from Resolved to Closed